

14. May 2020

Fact Sheet

70041801000000

M-Ltg-FU Q8/- 4x2, 5+2x2x1

KnorrTec

Kapellenbergstraße 34

D-93176 Beratzhausen

Tel. +49 (0) 9493 9519690

Fax +49 (0) 9493 9519679



Email: info@knorrtec.de

Web: www.knorrtec.de

motor cable shielded to fc,
 motor with/without brake, and/or thermal element,
 side 1: motor plug ISO23570-3 Typ 2(8 + PE),
 grommet housing angled, metal emv
 side 2: open
 cable design 4 x 2,5 mm² +2x2x 1mm²,
 PUR orange
 technical data contents
 Data sheet UPD00000600
 content of copper 0,23 kg/m + cutting allowance
 please insert length of cable seperately
 basic price plusx,xx € per meter
 + surcharges of material



Standard length	part no.
1,5 m	7xxxxxxx000150
3,0 m	7xxxxxxx000300
5,0 m	7xxxxxxx000500
10,0 m	7xxxxxxx001000

Pin assignement:

Pin Q8	-	wire
1	-	1
2	-	n. c.
3	-	3
4	-	5
5	-	7
6	-	6
7	-	2
8	-	8
PE	-	PE

.
 .
 ordering code for cable lenght
 7xxxxxxx00XXXX
 m cm

.
 .
 .
 useable for
 devices with interface according to ISO 23570
 e. g. Siemens ET200pro; G120D; G110D